

MHD PN SERIES

INDUSTRIAL VACUUMS



- ✓ Extremely silent.
- ✓ Large capacity detachable container. Forklift intakes.
- ✓ Integrated filter cleaning system

Suction Unit

Power	kW	7,5 - 18,5
Maximum depression	mmH2O	4.000 - 4.500
Continuous depression	mmH2O	2.600 - 3.200
Maximum air flow rate	m3/h	750 - 1.350

Filter Unit

Primary filter		Cartridge
Surface area - diameter	cm ² -mm	106.000 - 150
Number of cartridges		4
Filter media - class	IEC 60335-2-69	M ANT
Cleaning system		Automatic PN countercurrent air

Collection unit

Capacity	lt	160
----------	----	-----

Encumbrances

Dimensions	cm	163x76x200h
Weight	kg	332 - 430

APPLICATIONS: Sandblasting Cementitious



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

MHD PN SERIES

INDUSTRIAL VACUUMS

FILTER UNIT

The antistatic polyester stellar filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

COLLECTION UNIT

The steel container is equipped with a quick release system that allows for quick disposal of the vacuumed material.